



SFC 25/50/75

Stationary filter unit for in-duct mounting that mainly filters odours and gases by means of activated carbon filter cylinders with bayonet catch.

APPLICATIONS

The SFC range is intended to be used for the following applications:



- in-duct gas filter for inlet, outlet or recirculation of air (e.g. commercial buildings, process industry)
- mounting after an SFE unit as an odour filter in commercial kitchens

Do **not** use the SFC range for the following

- applications or in the following circumstances: • solids and liquids (like particles, smoke, grease, oil, etc.)




| • | explosive, | burning | and | aggressive | substances / | gase |
|---|------------|---------|-----|------------|--------------|------|
| | | | | | | |

SPECIFICATIONS

| | SFC-25 | SFC-50 | SFC-75 | | | | |
|------------------------------------|------------------------------------|-----------------|---------------|--|--|--|--|
| Physical dimensions and properties | | | | | | | |
| Heigth | 630 mm | 630 mm | 630 mm | | | | |
| Width | 450 mm | 900 mm | 1350 mm | | | | |
| Depth | 660 mm | 660 mm | 660 mm | | | | |
| Weight (net) | 63 kg | 106 kg | 160 kg | | | | |
| Material housing | aterial housing epoxy coated steel | | | | | | |
| Colour grey RAL 7035 | | | | | | | |
| Filters | | | | | | | |
| Cylinders | 8 (2 sets of | 16 (4 sets of 4 | 24 (6 sets of | | | | |
| | 4 pcs.) | pcs.) | 4 pcs.) | | | | |
| Holding frames | 1 | 2 | 3 | | | | |
| Recommended max. output | 1250 m³/h | 2500 m³/h | 3750 m³/h | | | | |
| Ambient conditions | | | | | | | |
| Max. operating temperature | 80°C | | | | | | |
| Max. relative humidity | 70% | | | | | | |
| Outdoor use allowed no | | | | | | | |
| Storage conditions • 5 - 50°C | | | | | | | |
| | relative humidity max. 70% | | | | | | |
| Scope of supply | | | | | | | |

- Unit housing incl. holding frame(s)
- Filter cylinders in box (sets of 4 pcs.)
- Manual

| | SFC-25 | SFC-50 | SFC-75 | | | | |
|--|--------------|-------------|------------|--|--|--|--|
| Order information | | | | | | | |
| Article number | | | | | | | |
| Airflow left-right | 1050053200 | 1050055200 | 1050057200 | | | | |
| Airflow right-left | 1050054200 | 1050056200 | 1050058200 | | | | |
| Housing / package | 1 | | | | | | |
| Boxes / package | 2 | 4 | 6 | | | | |
| Shipping data | | | | | | | |
| Gross weight (1 pc.) | 78 kg | 121 kg | 175 kg | | | | |
| Max. number / pallet | 6 | 3 | 3 | | | | |
| Packing dimensions | 80 x 130 x | 80 x 120 x | 80 x 160 x | | | | |
| | 210 cm | 210 cm | 210 kg | | | | |
| Gross weight | 393 kg | 333 kg | 495 kg | | | | |
| Harmonized Tariff Code | 8421.39.2090 | | | | | | |
| Country of origin | Netherlands | Netherlands | | | | | |



Air volumes are mentioned per filter cylinder. Recommended maximum output per cylinder is 156 m³/h.

Product type SFC-25/50/75 Product group Stationary filter units Version 12052015/0